



JET 230



basic data

volume to rim: 24,60 l
 weight: 545,00 g
 weight group: Medium
 Max. compression at 20 °C on the lowest pail: 52,00 kg


without handle: 0,00 g

tolerances

dimensions: +/- 1 mm
 volume/weight: +/- 5 %

dimensions

D1: 380,00 mm
 D2: 357,00 mm
 D3: 323,00 mm
 height: 270,00 mm




range JETP



decoration

height [mm]:
 width [mm]:
 median breadth [mm]:

IML	Offset
0,00	175,00
0,00	945,00
	1050,00



lids

DET 380

weight: 154,00 g
 Ø Lid [mm]: 376,00
 ISO volume: 23,00 l
 offset surface [mm]: 270,00
 IML surface [mm]: 279,00
 stacking height two fold [mm]:
 0,00
 stacking height each further
 [mm]: 0,00



stacking configuration / package


layer quantities: 6

Bucket

pieces per pallet: 216

Lid DET 380

pieces per pallet: 1296



material



QM / certificates



General Information

In our Technical Guidelines you will find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport.

Misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances and ink adhesion of the design, express reference is hereby made to our Technical Guidelines "Product" and "Design", which shall also form an integral part of the content of any delivery transaction. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. Technical modifications reserved.