



# JET 26



### basic data

volume to rim: 2,80 l  
 weight: 72,00 g  
 weight group: Medium  
 Max. compression at 20 °C on the lowest pail: 14,00 kg


plastic handle: 4,00 g

### tolerances

dimensions: +/- 1 mm  
 volume/weight: +/- 5 %

### dimensions

D1: 175,00 mm  
 D2: 163,00 mm  
 D3: 144,00 mm  
 height: 156,00 mm




### range JET



### decoration

height [mm]:  
 width [mm]:  
 median breadth [mm]:

IML	Offset
0,00	115,00
0,00	463,00
	478,00



### lids

#### DET 172

weight: 17,00 g  
 Ø Lid [mm]: 172,00  
 ISO volume: 2,70 l  
 offset surface [mm]: 125,00  
 IML surface [mm]: 151,50  
 stacking height two fold [mm]: 304,00  
 stacking height each further [mm]: 148,00



#### FDET 172

weight: 20,00 g  
 Ø Lid [mm]: 172,00  
 ISO volume: 2,80 l  
 offset surface [mm]: 0,00  
 IML surface [mm]: 0,00  
 stacking height two fold [mm]: 318,50  
 stacking height each further [mm]: 156,50



### stacking configuration / package

layer quantities: 30

#### Bucket


pieces per pallet: 1200

#### Lid DET 172

pieces per pallet: 6000

#### Lid FDET 172

pieces per pallet: 6000



### material



### QM / certificates



### General Information

In our Technical Guidelines you will find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport.

### Misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances and ink adhesion of the design, express reference is hereby made to our Technical Guidelines "Product" and "Design", which shall also form an integral part of the content of any delivery transaction. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. Technical modifications reserved.